


Watermark 30 high efficiency compact water softener



Description

High efficiency water softener with elegant design.
 Cabinet provided with sliding covers for the brine tank and display.
 This system is composed of a GRP vessel with top and bottom distributors and polyethylene cabinet.
 WATERMARK softeners are commanded by an automatic valve with a new generation controller with multilingual display and visual interface.
 High efficiency regenerations to reduce salt and water consumption.
 Holiday mode: During customer absences the system makes small cleanings without salt consumption.
 Connection 1".
 Brine valve included in the cabinet.
 Isolation by-pass and hardness mixer included.



Specifications

Min. pressure: 2.5 kg/cm².
 Max. pressure: 8.5 kg/cm².
 Min. temperature: 4 °C.
 Max. temperature: 35 °C.
 Power supply: 220 V - 12 Vac/50 Hz, other voltages available under request.

! Do not forget to order flexible metal hoses. Code 718601 (1")

Code	Description	Resin volume L	Connection	Exchange capacity °HFxm ³	Salt consumption kg	Working flow m ³ /h	Peak flow m ³ /h	Packaging units
795211	Watermark 30	30	1"	115 170 210	1.8 3.6 7.5	1.2	2.1	1



Code	Description	Packaging units
900601	1" male elbow adapter	1
900600	3/4" male elbow adapter	1

Water softeners

Watermark Installation example Domestic water softener Watermark-30



Private garage installation

Description	Code
1. Watermark 30 softener	795211
2. Filtermax pre-filter	723619
3. Sample intake valve	265000
4. Drainage	-
5. 1" Flexible hose	718601
6. Starfit 22 mm quick-connector bypass set	656805
7. Power supply 220 V	-